


SKYWORTH SECURITY




CONTENTS

- **About US**
- **Tools**
- **Product**
 - > **Super Dark Camera**
 - > **Wi-Fi Camera**
 - > **POE Tandem Camera**
 - > **Bullet & Turret Camera**
 - > **NVR**
- **Accessories**

SKYWORTH

Skyworth Group Co., Ltd. was founded in 1988, mainly engaged in multimedia business, smart system technology business, smart electrical appliances business, modern service business and other four major businesses, the group has two listed companies, Skyworth Group (HK00751) and Skyworth Digital (000810), several high-tech enterprises, with a national enterprise technology center, a national industrial design center.



2023

Skyworth Group
Fiscal Year Annual Results

Turnover of RMB **69,030** million



SKYWORTH DIGITAL


Skyworth Digital Co.,Ltd is a leading provider of home video entertainment and intelligent connectivity solutions. It is committed to leveraging cutting-edge technologies to develop and manufacture set-top boxes and network gateways to help video service providers and telecom carriers renovate customer access to Internet and video services. Today Skyworth Digital making ongoing investments in 5G, VR, IP and smart home technologies to help its clients address modern business challenges.

2023

Skyworth Digital
Fiscal Year Annual Results

Turnover of RMB **11,532** million

Skyworth Security is a leading provider of security products for the public and home security industry. Skyworth's products and solutions are widely deployed across homes, commercial buildings, schools, hospitals, parking spaces, and agricultural properties.



Supermarket



Farm



School



Factory



House

CORE CAPABILITY

ID / Industry Design

Skyworth Security has an excellent industrial design center, whose products have won many world-class design awards. The design department of Skyworth Security has been recognized as the "International Industrial Design Center"



Grand Slam for international top industrial design awards



SKYWORTH indoor PT camera

IDEA & iF awarded smart indoor camera, designed with a cute yellow crown on the top, which is a physical switch used to cover the camera lens when needed.



SKYWORTH outdoor PT camera

iF awarded Wi-Fi camera, designed for both indoor and outdoor situations. Featured with smart night vision, it is able to automatically shift from IR mode to color mode when detecting human at night, and turn back to IR mode after the person leaves. The shell design looks like a helmet, it implies the security of this product.

R&D / Research and Development

Skyworth Innovation Research Institute focuses on the research of cutting-edge technology and has in-depth research in AI, big data, edge computing, and other fields.

Skyworth Security's products have fully leveraged the advantage of the technology of Skyworth Innovation Research Institute, and have excellent performance in intelligent functions including but not limited to the function of human detection, motion detection, and human tracking.



Ten R & D centers all over the world provide a high degree of assurance for intelligent strategy.

London England	Deutschland Nürnberg	Istanbul Turkey	Thailand Bangkok	Indonesia Jakarta
India Noida	India Hyderabad	Johannesburg South Africa	Korea Seoul	China

SC / Supply Chain

Skyworth has 34 years of experience in electric product manufacture, Skyworth Security has built up its production workshop. Strict quality control and continuous optimization of production efficiency have made the products well received in the market. Relying on Skyworth's globe manufacturing center, Skyworth benefits its customers via local manufacturing.



Guadalajara, Mexico
Nuremberg, Germany
Johannesburg, South Africa
Chennai, India
Bangkok, Thailand
Jakarta, Indonesia
Shenzhen, China ...




CUSTOMER

Invested in long term relationships with our clients, built on mutual respect. Matching our client's business strategy to our product roadmap.





AI Home Camera

AI Home Camera is a mobile APP that can easily manage cameras and network video recorders (e.g. live view, playback, settings and functions, etc.). The GUI of AI Home Camera is reasonable and interactive, making it easy for both novice users and professional installers to get started. The APP supports both Android and iOS system, thus the users can download it from the corresponding application store.




AI CAM

AI CAM is the software used to manage devices on TVs (Android systems). Users can check the live view and playback of the camera on the large screen. The software also supports PIP function, which allows users to view the image of the camera while watching the TV.





VMS

VMS is the software that manages devices on the PC side. It supports adding and managing cameras and NVRs through LAN and the Internet. Users can view and set the camera in real time on the VMS (e.g. detection and alarm functions, etc.). VMS supports Windows system.



Super Dark Camera

Equipped with the cutting-edge artificial intelligence image technology, SKYWORTH super dark series can show vivid color video even in ultra low-light circumstance. AI detection function also available in the series.




Conventional camera




SKYWORTH Super Dark Camera

5MP Super Dark Bullet Camera




Main Specification	Model	SKH-I55B4S
	Resolution	5MP
	Aperture	F1.0
	Focal Length	4mm
	Audio	Audio Out*1 + Built-in MIC
	Night Vision	Super Dark Vision
	Certificate	CE, EAC, RoHS
	FOV	H - 95° / V - 51.5° / D - 112°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A or POE 48V/0.35A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	Metal
	Dimension	95*95*225mm
	Net Weight	About 805g
	Gross Weight	About 1009g
	IP Grade	IP67
	Installation	Hoisting / Wall Mounting


5MP Super Dark Wi-Fi Camera




5MP FHD




Full Color




Human Tracking




Two-way Audio




Wi-Fi Connection




F1.0




Vehicle Detection



AI-ISP



1/1.79" CMOS



2Tops



Main Specification	Model	SKH-I65B4S
	Resolution	5MP
	Aperture	F1.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	Super Dark Vision
	Certificate	CE, EAC, NTRA, RoHS
	FOV	H - 95° / V - 51.5° / D - 112°
	Ethernet	1*10/100Mbps (RJ45)
	TF	Max. 512G
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, 2.4G Wi-Fi, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~45℃
	Material	PC
	Dimension	129*129*34mm
	Net Weight	About 656g
	Gross Weight	About 995g
	IP Grade	Indoor and Outdoor
	Installation	Hoist / Wall / Rod Mounting

Wi-Fi Camera



SKYWORTH sells more than 50,0000 units of product which have built-in Wi-Fi module annual year, so we have the state-of-the-art Wi-Fi technology and much experience in this sector. Our Wi-Fi lab can do the conduction test, throughput test, TIS/ERP test, etc. To conclude, SKYWORTH Wi-Fi camera shows a stable network performance in various environments.

Benefit from years of experience in the consumer electronics industry, our products have been optimized and designed to be user-friendly, which makes the end user start to use our product easily. In additional, the camera can be controlled not only by mobile phone but also in Google TV or Android TV box when you install AI Cam from Google TV app store.



Skyworth Smart Screen Home Camera A50

Witnessing the Strength of the Companionship



Touch screen



Two-way video call




12x smart zoom



Artificial intelligence



5MP Smart Screen Home Camera



Main Specification	Model	A50
	Resolution	5MP
	FOV	H - 91° / V - 46° / D - 109°
	Aperture	F1.6
	Focal Length	4mm
	Audio	Built-in MIC & Speaker
	Night Vision	IR / Super Dark Vision
	Certificate	CE, RoHS
	Material	PC+ABS
	Network	2.4G & 5G WI-FI
IVS	Smart Alarm	Motion Detection / Human Detection / Pet Detection / Fall Detection / Sound Detection / Fire Detection
	Video Call	Touch Screen / App / Gesture Control
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP/IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP/RTSP
	APP	AI Home Camera
General Specification	Screen Size	2.4 Inch
	Power	Type-C 5V / 1.5A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5℃~40℃
	Power Consumption	Max. 7.5W
	Dimension	80*80*160mm
	Package Size	111*218*91mm
	Net Weight	About 337g
	Gross Weight	About 695g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

3MP Smart Wi-Fi Camera With RJ45 Port



3MP FHD




2.4Ghz Wi-Fi 6



Dual-Light Vision



Wi-Fi / RJ45


Physical Privacy
Masking


Pan-Tilt



Two-way Audio




APP Control



Main Specification	Model	H30P
	Resolution	3MP
	FOV	H - 80° / V - 42° / D - 95°
	Aperture	F1.6
	Focal Length	4mm
	Audio	Built-in Mic & Speaker
	Night Vision	Dual-light Vision
	Certificate	CE, RoHS
	Privacy Masking	Yes (via physical buttons)
	Network	Wi-Fi 2.4GHz (Wi-Fi 6 - 802.11b/g/n/ax) + RJ45
IVS	Smart Alarm	Motion Detection / Human Detection
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP/IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP/RTSP
	APP	AI Home Camera
General	Power	Type-C 5V / 1A
	Working Humidity	<90% (non- condensing)
	Working Temperature	-5℃~40℃
	Power Consumption	Max. 5W
	Dimension	82*82*111.8mm
	Net Weight	About 188g
	Gross Weight	About 335g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

3MP Indoor Smart Wi-Fi Camera




Main Specification	Model	H30C
	Resolution	3MP
	Aperture	F2.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, RoHS
	FOV	H - 75° / V - 42° / D - 89°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	/
	Network	2.4G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	117.5*66.9mm
	Net Weight	About 74g
	Gross Weight	About 273g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

3MP IR Wi-Fi Camera




Main Specification	Model	H30
	Resolution	3MP
	Aperture	F2.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, NTC, NTRA, RoHS
	FOV	H - 80° / V - 43° / D - 95°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	Profile S
	Network	2.4G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	107*73mm
	Net Weight	About 170g
	Gross Weight	About 370g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

4MP IR Wi-Fi Camera




Main Specification	Model	H40
	Resolution	4MP
	Aperture	F2.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, EAC, NTC, RoHS, REACH, WEEE
	FOV	H - 80° / V - 43° / D - 95°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	Profile S
	Network	2.4G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	107*73mm
	Net Weight	About 168g
	Gross Weight	About 366g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

4MP IR Dual-band Wi-Fi Camera




Main Specification	Model	H40 Pro
	Resolution	4MP
	Aperture	F2.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, FCC ID, NTC, RCM, RoHS, REACH, WEEE
	FOV	H - 80° / V - 44° / D - 83°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	Profile S
	Network	2.4G & 5G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1A
	Working Humidity	<90%(non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	107*73mm
	Net Weight	About 168g
	Gross Weight	About 366g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

5MP IR Dual-band Wi-Fi Camera



Main Specification	Model	H50 Pro
	Resolution	5MP
	Aperture	F2.0
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, FCC ID, NTC, RCM, RoHS, REACH, WEEE
	FOV	H - 73° / V - 44° / D - 85°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	Profile S
	Network	2.4G & 5G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1A
	Working Humidity	<90%(non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	107*73mm
	Net Weight	About 168g
	Gross Weight	About 366g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

8MP IR Dual-band Wi-Fi Camera



Main Specification	Model	H80 Pro
	Resolution	8MP
	Aperture	F1.6
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	IR
	Certificate	CE, FCC ID, NTC, RoHS, REACH, WEEE
	FOV	H - 90° / V - 46° / D - 107°
	Ethernet	Null
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection
Others	Language	English
	ONVIF	Profile S
	Network	2.4G & 5G Wi-Fi
	APP	AI Home Camera
General Specification	Power	Type-C 5V/1.5A
	Working Humidity	<90%(non-condensing)
	Working Temperature	-5℃~40℃
	Material	PC
	Dimension	107*73mm
	Net Weight	About 187g
	Gross Weight	About 404g
	IP Grade	Indoor
	Installation	Horizontal / Ceiling

4MP Dual-light Wi-Fi Camera



Main Specification	Model	SKH-I64D8P
	Resolution	4MP
	Aperture	F1.6
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	Dual-light Vision
	Certificate	CE, RoHS
	FOV	H - 80° / V - 41° / D - 86°
	Ethernet	1*10/100Mbps (RJ45)
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, 2.4G Wi-Fi, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~45℃
	Material	PC
	Dimension	144*144*359mm
	Net Weight	About 632g
	Gross Weight	About 978g
	IP Grade	Indoor and Outdoor
	Installation	Ceiling / Rod / Wall Mounting

3MP Dual-light Wi-Fi Camera



Main Specification	Model	SKH-I63D4H2
	Resolution	3MP
	Aperture	F1.6
	Focal Length	4 mm
	Audio	Built-in MIC and Speaker
	Night Vision	Dual-light Vision
	Certificate	CE, NTC, NTRA, RoHS
	FOV	H - 88.5° / V - 45° / D - 105°
	Ethernet	1*10/100Mbps (RJ45)
	TF	Max. 512G
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, 2.4G Wi-Fi, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~45℃
	Material	PC
	Dimension	129*129*340mm
	Net Weight	About 349g
	Gross Weight	About 614g
	IP Grade	Indoor and Outdoor
	Installation	Ceiling / Rod / Wall Mounting

POE Tandem Camera

Beyond tradition, SKYWORTH POE tandem camera is equipped with one fixed lens working as fixed guard, plus one panoramic lens being responsible for tracking & patrolling. The dual-lens AI linkage allows the two lens collaboratively work to present a larger FOV than the traditional bullet camera or PTZ camera. Meanwhile, thanks to the 12x smart zoom, the panoramic lens is able to provide a far sight when needed. In addition, it supports POE power supply, therefore the power cord becomes unnecessary.



The PTZ camera now has a wider view



POE Tandem Camera



4MP + 4MP



Dual-light Vision



Human Tracking




Two-way Audio



Dual-lens AI Linkage



Vehicle Detection



POE



12x Smart Zoom

Main Specification	Model	SKH-I88DYP-46CPT
	Resolution	4MP (fixed) + 4MP (PTZ)
	Aperture	F1.6
	Focal Length	3.6mm (fixed) / 6mm (PTZ)
	Audio	Built-in Mic and Speaker
	Night Vision	Dual-Light Vision
	FOV	H - 79° / V - 44° / D - 92° (fixed), H - 51° / V - 29° / D - 59° (PTZ)
	Ethernet	1* 10/100Mbps (RJ45)
	TF	Max. 512G
IVS	Smart Alarm	Human Detection & Tracking / Vehicle Detection / Motorbike Detection / Motion Detection / Tandem View
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	POE 48V/0.25A or DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~45℃
	Material	PC
	Dimension	144*186*360mm
	Net Weight	About 730g
	Gross Weight	About 1487g
	IP Grade	Indoor / Outdoor
	Installation	Ceiling / Rod / Wall Mounting
	Packing List	Camera*1 Waterproof Kit*1 Power Adapter*1 Positioning Sticker*1 Screw and Anchor Pack*1 Quick Start Guide*1 Ethernet Cable (5 meters)*1 Ethernet Cable (18 meters)*1

Bullet & Turret Camera

SKYWORTH bullet and turret camera with built-in MIC and POE make things easier since the trouble of deploying power cord and MIC has disappeared. Also the AI function such as human / motion detection is the standard feature thanks to our own AI innovation institution.



Dual-light series camera shows smart night vision at night, it can be set as IR night mode whose video color is black&white, Full color mode whose video is colourful, Smart night mode which can change the mode according to the AI algorithm.

Smart Night Mode



In dark environment, the camera launch the IR light by default.




Once a person / vehicle comes into the view of the camera, the camera will launch the warm light and record a short video if configured.



As the person / vehicle comes away, the camera will turn back to IR light again.

3MP Dual-light Bullet Camera




Main Specification	Model	SKH-I53D8H
	Resolution	3MP
	Aperture	F1.6
	Focal Length	4mm / 6mm (optional)
	Audio	Built-in MIC
	Night Vision	Dual-light Vision
	Certificate	CE, EAC, RoHS
	FOV	4mm: H - 82° / V - 45° / D - 96.5°, 6mm: H - 50° / V - 28° / D - 58°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A or POE 48V/0.35A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	203*83*82mm
	Net Weight	About 300g
	Gross Weight	About 451g
	IP Grade	IP67
	Installation	Hoisting / Wall Mounting

3MP IR Bullet Camera



Main Specification	Model	SKH-I53R8H
	Resolution	3MP
	Aperture	F2.0
	Focal Length	4mm / 6mm (optional)
	Audio	Built-in MIC
	Night Vision	IR Night Vision
	Certificate	CE, EAC, RoHS
	FOV	4mm: H - 80° / V - 44° / D - 93°, 6mm: H - 51° / V - 29° / D - 58°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A or POE 48V/0.35A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	203*83*82mm
	Net Weight	About 302g
	Gross Weight	About 452g
	IP Grade	IP67
	Installation	Hoisting / Wall Mounting

5MP Dual-light Bullet Camera



Main Specification	Model	SKH-I55D8H
	Resolution	5MP
	Aperture	F1.6
	Focal Length	4mm / 6mm (optional)
	Audio	Built-in MIC
	Night Vision	Dual-light Vision
	Certificate	CE, EAC, RoHS
	FOV	4mm: H - 82° / V - 43° / D - 94°, 6mm: H - 51° / V - 28° / D - 57°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A or POE 48V/0.35A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	203*83*82mm
	Net Weight	About 300g
	Gross Weight	About 473g
	IP Grade	IP67
	Installation	Hoisting / Wall Mounting

5MP IR Bullet Camera



5MP FHD



H.265+



Human Detection



Vehicle Detection



Built-in MIC



APP Control



IP67



Main Specification	Model	SKH-I55R8H
	Resolution	5MP
	Aperture	F2.0
	Focal Length	4mm / 6mm (optional)
	Audio	Built-in MIC
	Night Vision	IR Night Vision
	Certificate	CE, EAC, RoHS
	FOV	4mm: H - 74° / V - 40° / D - 88°, 6mm: H - 48° / V - 27° / D - 56°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/1A or POE 48V/0.35A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	203*83*82mm
	Net Weight	About 295g
	Gross Weight	About 449g
	IP Grade	IP67
	Installation	Hoisting / Wall Mounting

3MP IR Turret Camera



3MP FHD



H.265+



Human Detection



Built-in MIC




APP Control




Main Specification	Model	SKH-I43R2H2
	Resolution	3MP
	Aperture	F2.0
	Focal Length	2.8mm / 4mm (optional)
	MIC	Built-in MIC
	Night Vision	IR
	Certificate	CE, EAC, RoHS, REACH, WEEE
	FOV	2.8mm: H - 93° / V - 52° / D - 99°, 4mm: H - 76° / V - 41° / D - 89°
	Ethernet	1*10/ 100Mbps (RJ45, POE)
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	POE 48V/0.35A or DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	99*99*83mm
	Net Weight	About 167g
	Gross Weight	About 264g
	IP Grade	Indoor
	Installation	Hoist / Ceiling / Wall Mounting

3MP Dual-light Turret Camera




Main Specification	Model	SKH-I43D2H
	Resolution	3MP
	Aperture	F1.6
	Focal Length	2.8mm / 4mm (optional)
	MIC	Built-in MIC
	Night Vision	Dual-light Vision
	Certificate	CE, EAC, RoHS
	FOV	2.8mm: H - 101° / V - 54° / D - 119.5°, 4mm: H - 82° / V - 45° / D - 97°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	POE 48V/0.35A or DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	99*99*83mm
	Net Weight	About 273g
	Gross Weight	About 391g
	IP Grade	Indoor
	Installation	Hoist / Ceiling / Wall Mounting

5MP IR Turret Camera



Main Specification	Model	SKH-I45R2H
	Resolution	5MP
	Aperture	F2.0
	Focal Length	2.8mm / 4mm (optional)
	MIC	Built-in MIC
	Night Vision	IR
	Certificate	CE, RoHS, REACH
	FOV	2.8mm: H - 94° / V - 51° / D - 108°, 4mm: H - 75° / V - 42° / D - 87°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	POE 48V/0.35A or DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20℃~60℃
	Material	PC
	Dimension	99*99*83mm
	Net Weight	About 167g
	Gross Weight	About 264g
	IP Grade	Indoor
	Installation	Ceiling / Hoist / Wall Mounting

5MP Dual-light Turret Camera



Main Specification	Model	SKH-I45D2H
	Resolution	5MP
	Aperture	F1.6
	Focal Length	2.8mm / 4mm (optional)
	MIC	Built-in MIC
	Night Vision	Dual-light Vision
	Certificate	CE, RoHS, REACH
	FOV	2.8mm: H - 96° / V - 54° / D - 101°, 4mm: H - 79° / V - 44° / D - 92°
	Ethernet	1*10/100Mbps (RJ45, POE)
IVS	Smart Alarm	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	POE 48V/0.35A or DC 12V/1A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-20°C~60°C
	Material	PC
	Dimension	99*99*83mm
	Net Weight	About 274g
	Gross Weight	About 388g
	IP Grade	Indoor
	Installation	Ceiling / Hoist /Wall Mounting



Network Video Recorder

SKYWORTH network video recorder, support the connection of up to 4CH/6CH/8CH/10CH/16CH/25CH/36CH IP cameras, with the Max. 4CH/16CH (main stream) playback at same time under the help of HDD. What amazing is that SKYWORTH NVR is able to add cameras (in the same LAN) with different IP segments.

In general, cameras with different IP segments can't get connected with the recorder and play video. If you want to check the video of the camera on the monitor via NVR, you need to ensure that the IP segment of the camera and NVR are the same. However, things change when you use SKYWORTH NVR, since the camera with different IP segments is able to directly play video on the NVR!



Solutions



6/10/16CH Network Video Recorder



Cloud Playback



H.265+



4K HDMI Output



Support 8T HDD



Add Camera
across IP
Segments



APP Control



Main Specification	Model	SKH-N106K-A (6CH) & SKH-N110K-A (10CH) & SKH-N116K-A (16CH)
	Resolution	Max. 8MP
	Channel	Max. 6/10/16CH
	Panel	1/4/6/8/9/10/12/16 Panel
	IPC Connection	6CH*8MP / 10CH*8MP / 16CH*8MP
	Live View	1 Panel: 1CH*8MP 4 Panel: 4CH*4MP 6 Panel: 2CH*5MP + 4CH*720P 8 Panel: 2CH*5MP + 6CH*720P 9 Panel: 2CH*5MP + 7CH*720P 10 Panel: 4CH*4MP + 6CH*3MP 12 Panel: 4CH*4MP + 8C *3MP 16 Panel: 4CH*4MP + 12CH*3MP
	Playback	1 Panel: 1CH*8MP 4 Panel: 4CH*4MP
	Incoming Bandwidth	512Mbps
	Outgoing Bandwidth	512Mbps
	Audio	Audio Out*1
	Certificate	CE, EAC, RoHS, REACH, WEEE
	Material	Metal
	Ethernet	1*10/100Mbps (RJ45)
	HDD	Support Max. 8T HDD*1
Alarm	IPC side	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
	NVR side	Video loss / HDD error / HDD full / No HDD / IP conflict
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/2A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5 ~45
	Power Consumption	Max. 24W
	Dimension	280*208*51mm
	Net Weight	About 692g
	Gross Weight	About 1137g
	IP Grade	Indoor

25/36CH Network Video Recorder




Cloud Playback



H.265+



4K HDMI Output



Support 10T HDD



Add Camera
across IP
Segments



APP Control



Main Specification	Model	SKH-N225K-A (25CH) & SKH-N236K-A (36CH)
	Resolution	Max. 8MP
	Channel	Max. 25/36CH
	Panel	1/4/6/8/9/10/12/16/25/36 Panel
	IPC Connection	25CH*8MP / 36CH*8MP
	Live View	1 Panel: 1CH*8MP 4 Panel: 2CH*8MP + 2CH*4MP 6 Panel: 6CH*5MP 8 Panel: 8CH*5MP 9 Panel: 8CH*5MP + 1CH*3MP 10 Panel: 8CH*5MP + 2CH*3MP 12 Panel: 8CH*5MP + 4CH*3MP 16 Panel: 16CH*4MP 25 Panel: 16CH*4MP + 9CH*3MP 36 Panel: 16CH*4MP + 20CH*720P
	Playback	1 Panel: 1CH*8MP 4 Panel: 4CH*5MP 8 Panel: 8CH*5MP 16 Panel: 16CH*4MP
	Incoming Bandwidth	768Mbps
	Outgoing Bandwidth	768Mbps
	Audio	Audio Out*1 + Audio In*1
	Certificate	CE, RoHS, EAC
	Material	Metal
	Ethernet	1*10/100Mbps (RJ45) + 1*10/100/1000Mbps (RJ45)
	HDD	Support Max. 10T HDD*2
Alarm	IPC side	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
	NVR side	Video loss / HDD error / HDD full / No HDD / IP conflict
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 12V/4A
	Working Humidity	<90% (non-condensing)
	Working Temperature	-5 ~40
	Power Consumption	Max. 48W
	Dimension	325*243*54mm
	Net Weight	About 1160g
	Gross Weight	About 1857g
	IP Grade	Indoor

POE Network Video Recorder



Cloud Playback



H.265+



4K HDMI Output



POE for Camera



Support 8T HDD



Add Camera
across IP
Segments



APP Control



Main Specification	Model	SKH-N104K-AP (4CH) / SKH-N108K-AP (8CH)
	Resolution	Max. 8MP
	Channel	Max. 4/8CH
	Panel	1/4/6/8 Panel
	IPC Connection	4CH*8MP / 8CH*8MP
	Live View	1 Panel: 1CH*8MP 4 Panel: 4CH*4MP 6 Panel: 2CH*5MP + 4CH*720P 8 Panel: 2CH*5MP + 6CH*720P
	Playback	1 Panel: 1CH*8MP 4 Panel: 4CH*4MP
	Incoming Bandwidth	512Mbps
	Outgoing Bandwidth	512Mbps
	Audio	Audio Out*1+Audio In*1
	Certificate	CE, EAC, RoHS, REACH, WEEE
	Material	Metal
	Ethernet	1 (10/100Mbps, RJ45)
	POE	4CH (10/100Mbps, RJ45) / 8CH (10/100Mbps, RJ45)
	HDD	Support Max. 8T HDD*1
Alarm	IPC side	Human & Vehicle Detection / Motion Detection / Area Detection / Line Crossing
	NVR side	Video loss / HDD error / HDD full / No HDD / IP conflict
Others	Language	English / German / French / Spanish / Arabic / Russian / Vietnamese / Italian / Japanese / Turkish
	ONVIF	Profile S
	Protocol	TCP / IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, P2P
	APP	AI Home Camera
General Specification	Power	DC 48V/2A
	Working Humidity	< 90% (non-condensing)
	Working Temperature	-5℃~40℃
	Dimension	280*208*51mm
	Net Weight	About 774g (4CH) / 816g (8CH)
	Gross Weight	About 1798g (4CH) / 1878g (8CH)
	IP Grade	Indoor

POE Network Video Recorder Kit

Model	SKH-K554PN8	
Kit Type	SKH-I55D8H	4
	SKH-N108K-AP	1
Accessories	Ethernet Cable	5m * 1 + 18m * 4
	HDMI Cable	1.5m * 1
	Power Adapter	DC 48V/2A * 1 (for NVR)
	Mouse	1 (for NVR)
	Quick Start Guide	1
	Positioning Sticker	4 (for cameras)
	Waterproof Kit	4 (for cameras)
	Installation Screw	1 set (for HDD) + 4 set (for cameras)
Certificate	CE, RoHS	
Gross Weight	5.8kg	
Dimension	380*375*330mm	



Model	SKH-K454PN8	
Kit Type	SKH-I45D2H	4
	SKH-N108K-AP	1
Accessories	Ethernet Cable	5m * 1 + 18m * 4
	HDMI Cable	1.5m * 1
	Power Adapter	DC 48V/2A * 1 (for NVR)
	Mouse	1 (for NVR)
	Quick Start Guide	1
	Positioning Sticker	4 (for cameras)
	Waterproof Kit	4 (for cameras)
	Installation Screw	1 set (for HDD) + 4 set (for cameras)
Certificate	CE, RoHS	
Gross Weight	5.7kg	
Dimension	380*375*304mm	

Model	SKH-KM54PN8	
Kit Type	SKH-I55D8H	2
	SKH-I45D2H	2
	SKH-N108K-AP	1
Accessories	Ethernet Cable	5m * 1 + 18m * 4
	HDMI Cable	1.5m * 1
	Power Adapter	DC 48V/2A * 1 (for NVR)
	Mouse	1 (for NVR)
	Quick Start Guide	1
	Positioning Sticker	4 (for cameras)
	Waterproof Kit	4 (for cameras)
	Installation Screw	1 set (for HDD) + 4 set (for cameras)
Certificate	CE, RoHS	
Gross Weight	5.79kg	
Dimension	380*375*330mm	




Accessories

SKYWORTH provides the whole solution of security system include not only cameras and NVRs, but also the related accessories like junction box (for camera installation), network cable (RJ45), POE network switch and POE adapter.



In general, the accessories will be applied to complement the product, thus forming a complete solution and simplifying the installation of cameras or NVRs. For example, the POE switch and network cable help the NVR (non-POE) to connect the POE cameras without deploying the power cord for the cameras; POE adapter combines the network transmission and power supply to a single connection etc.. These accessories need to be ordered separately.



Waterproof Junction box



Model	SKH-CXH001	
Structure	Product Material	Aluminum Alloy
	Net Weight	0.25kg (0.55 lb)
	Gross Weight	0.32kg (0.71 lb)
Environment	Ambient Temperature	-20°C to 60°C
	Humidity	< 90% (RH)
Compatible Models	SKH-I53R8H/SKH-I53D8H SKH-I55R8H/SKH-I55D8H SKH-I55B4S SKH-I43R2H2/SKH-I43D2H SKH-I45R2H/SKH-I45D2H	
IP Grade	IP66	
Certificate	RoHS	

POE Adapter

Model	SKH POEADP01	
Main Specification	Input	100~240V AC, 0.5A, 50/60Hz
	Output	48V/0.25A
Protection	Short Circuit Protection	Support
	Over Current Protection	Support
	Over Voltage Protection	Support
Environment	Working Temperature	-10°C to 45°C
	Storage Temperature	-20°C to 70°C
	Humidity	< 95% (RH)
Certificate	CE, RoHS	



POE Network Switch

Model	SKH-POESW08 (8-channel POE) / SKH-POESW16 (16-channel POE)	
Main Specification	Input	SKH-POESW08: 110~240V AC, MAX 2.5A, 50/60Hz SKH-POESW16: 110~240V AC, MAX 2.7A, 50/60Hz
	POE Output	SKH-POESW08: 52V/2.3A, Max. 30W / POE port SKH-POESW16: 52V/4.8A, Max. 30W / POE port
POE	Standard	IEEE 802.3af/at
	Transmission	≤250 meters
	Cable	10/100/1000BASE-TX: UTP cable (CAT5 or above)
Environment	Working Temperature	-10°C to 55°C
	Storage Temperature	-40°C to 85°C
	Humidity	< 90% RH (non-condensing)
Certificate	CE, RoHS	



305M UTP Cable



Model	SKH-T5E-UTP01 (CAT5E) / SKH-T06-UTP01 (CAT6)	
Conductor	Material	CCA (copper content: 50%)
	Diameter	CAT5E: 0.5mm +0.05mm / -0mm CAT6: 0.57mm +0.05mm / -0mm
Jacket	Material	PVC (white)
	Diameter	CAT5E: 5.2 +0.2mm / -0.2mm CAT6: 6.2 +0.2mm / -0.2mm
General	Working Temperature	-20°C to 60°C
	Humidity	< 60% (RH)
	Cable Length	305.0 m ± 2 m
Certificate	CE, RoHS	

Contact Us



Skyworth CCTV

The Information Security Is Our Priority

